




GEISER 130 is a LED recessed lamp ideal for outdoor signal lighting. This LED floor - recessed lamp is ideal for creating guide lights which highlight the paths in gardens and building areas even near the sea or salt water. This luminaire features IP67 that gives high protection against rain and solids. Can be directed once installed and has ANTI - GLARE accessory.



General characteristics

| | |
|------------------------|-----------|
| Fixation | Floor |
| Type | I |
| IP | 67 |
| voltage | 220V-240V |
| Hertz | 50/60Hz |
| included battery | . |
| Horizontal orientation | ↻ 20 |
| Flush box | Yes |
| Flush box dimensions | ø90x135mm |
| Power | 6.5W |
| IK | 08 |
| Cutting size | ø90mm |

Material

| | |
|----------------|--------------------------------|
| Body/Structure | Stainless steel 316L+Aluminium |
| Diffuser | Glass |

Finish

| | |
|----------------|-----------------|
| Body/Structure | Satin Stainless |
| Diffuser | Transparent |

Lighting characteristics

| | |
|---------------------------|-----------------|
| Light source included | Yes |
| Maximum ceiling thickness | 10 |
| Temperature | 3000K |
| | |
| MacAdam Steps | 5 SDCM |
| LM | 400lm |
| CRI | >80 |
| LED lifetime | LM80 |
| Degrees of light aperture | 38° |
| Weight supported | 2000Kg |
| Light direction | Accent lighting |
| Energy classification | F |

Driver

| | |
|-----------------|-----|
| Requires Driver | Yes |
| Driver embedded | Yes |

File download

| | |
|-------------------|-------------------------------|
| General documents | Download > |
| Images | Download > |
| 2D / 3D | Download > |
| | Download > |
| BIM | Download > |

